

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

DATE MAILED: 08/23/2006

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/666,730	09/22/2003	Hidetoshi Naruki	L8734.03102	6048
24257 75	590 08/23/2006		EXAM	INER
	AVIS MILLER & M	MALKOWSKI, KENNETH J		
1615 L STREE SUITE 850	T, NW	ART UNIT	PAPER NUMBER	
WASHINGTO:	N, DC 20036	2613		

Please find below and/or attached an Office communication concerning this application or proceeding.

			,	,
_		1	۲	•
7	_	7	•	

	Application No.	Applicant(s)				
	10/666,730	NARUKI ET AL.				
Office Action Summary	Examiner	Art Unit				
•	Kenneth J. Malkowski	2613				
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address				
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period w - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	TE OF THIS COMMUNICATION 6(a). In no event, however, may a reply be tim ill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 22 Se	eptember 2003.					
, <u> </u>						
closed in accordance with the practice under E	x parte Quayle, 1935 C.D. 11, 45	53 O.G. 213.				
Disposition of Claims						
4) Claim(s) is/are pending in the application	n.					
4a) Of the above claim(s) is/are withdrawn from consideration.						
5) Claim(s) is/are allowed.						
6)⊠ Claim(s) <u>1-6</u> is/are rejected.						
7) Claim(s) is/are objected to.						
8) Claim(s) are subject to restriction and/or	election requirement.					
Application Papers						
9) The specification is objected to by the Examine	r.					
10)⊠ The drawing(s) filed on 22 September 2003 is/a	re: a)⊠ accepted or b)⊡ objec	ted to by the Examiner.				
Applicant may not request that any objection to the	drawing(s) be held in abeyance. See	e 37 CFR 1.85(a).				
Replacement drawing sheet(s) including the correcti						
11) ☐ The oath or declaration is objected to by the Ex	aminer. Note the attached Office	Action or form PTO-152.				
Priority under 35 U.S.C. § 119						
12)⊠ Acknowledgment is made of a claim for foreign a)⊠ All b)□ Some * c)□ None of:	priority under 35 U.S.C. § 119(a))-(d) or (f).				
1. Certified copies of the priority documents have been received.						
2. Certified copies of the priority documents have been received in Application No						
3. Copies of the certified copies of the priority documents have been received in this National Stage						
application from the International Bureau (PCT Rule 17.2(a)).						
* See the attached detailed Office action for a list of the certified copies not received.						
Attachment(s)	A) [] (max.)	(DTO 412)				
Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948)	4) Interview Summary Paper No(s)/Mail Da					
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date	5) Notice of Informal P 6) Other:	atent Application (PTO-152)				

Application/Control Number: 10/666,730

Art Unit: 2613

DETAILED ACTION

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 2. Claims 1-3 are rejected under 35 U.S.C. 102(e) as being anticipated by U.S. Patent No. 6,504,634 to Chan et al.

With respect to claim 1, Chan discloses an optical wireless communication system (column 5 lines 55-64 (nodes are interconnected with one another by optical communication links, it is preferable that said links are wireless communication links)) including a transmitter (1004, Figure 18) having a first optical transmitting means for transmitting a first optical signal having narrow directivity (column 21 lines 40-49 (narrow beam width signal narrow beam waist and a small divergence)) and a receiver (1002, Figure 18) having a first optical receiving means for receiving said first optical signal (column 5 lines 57-58 (nodes include one or more optical transmitters and receivers)) and converting said first optical signal into an electric signal (column 6 lines 10-11 (receivers use photodetectors)), wherein said receiver comprising: light-receiving level detecting means for detecting a light-receiving level of said first optical signal received by said first optical receiving means (column 6 lines 10-11 (receivers use

Page 3

photodetectors)); second optical transmitting means for transmitting a second optical signal (1008, figure 18) which carries light-receiving level information of said first optical signal obtained by said light-receiving level detecting means (column 34 lines 44-48 (signal strength received by receiver can provide said signal strength information back to the transmitter)) and has directivity wider than that of said first optical signal (column 28 lines 14-16 (a second transmitter 1008 has a wider beam of divergence than the first transmitter)); said transmitter comprising: a second optical receiving means (1010, Figure 18)(column 27 lines 62-65 (a second optical transmitter and receiver pair are included at either end of the communication link to facilitate alignment of the optical components) including a plurality of light-receiving elements each having light-receiving capability for receiving said second optical signal at a level corresponding to the direction of said receiver (Figure 19)(column 30 lines 28-31 (quadrant detector with four quadrants))(column 28 lines 24-26 (quadrant detector offers spatial information about the received signal)); a drive means (column 10 lines 5-6 driving mechanics))(column 10 lines 39-44 (motor or other drive mechanism can be used to drive the gimbals)) for positioning said first optical transmitting means and said second optical receiving means by integrally shifting said first optical transmitting means and said second optical receiving means toward the direction of said receiver (column 11 lines 20-28 (pointing offset error is corrected by using drive means to correct for pointing error))(column 2 lines 13-19 (transceivers are fixed to a movable mount to facilitate pointing of a transceiver to another node in the network))(column 3 lines 25-28 (pointing of the transmitter can be adjusted)); rough optical axis adjusting (column 27 47-50 (link

Art Unit: 2613

acquisition)) means for executing a rough optical axis adjustment by controlling said drive means so as to eliminate a difference in the light-receiving level of said plurality of light-receiving elements of said second optical receiving means (column 37 lines 1-7 (the initial step of alignment is rough or course pointing)); fine optical axis adjusting means for executing a fine optical axis adjustment (column 27 lines 57-61 (higher degree of pointing precision))(column 37 lines 25-30 (transmitter begins scan which is at worst a 10 degree by 10 degree uncertainty field wherein transmit beam can be centered on detector)) by controlling said drive means based on the light-receiving level information contained in the second optical signal being received by said second optical receiving means, after the rough optical axis adjustment by said rough optical axis adjusting means is accomplished (column 37 lines 14-31 (coarse pointing may not be enough to adequately acquire the transmitted signal, in this case finer adjusting is used))(column 35 lines 36-40 (if the received signal passes a threshold the transmitter is slewing in the correct direction to provide more accurate centering))(Figure 26).

With respect to claim 2, Chan discloses the optical wireless communication system in accordance with claim 1, wherein said plurality of light-receiving elements of said second optical receiving means are four photoelectric conversion elements arranged in a matrix pattern consisting of two lines and two rows in horizontal and vertical directions (column 11 lines 14-27 (quadrant PIN detector))(Figure 19 (two rows and two columns shown)), Figure 21 (two rows and two columns shown)), and said rough optical axis adjusting means executes the rough positioning of the optical axis in a total of eight directions based on the difference in the light-receiving level of said four

Art Unit: 2613

photoelectric conversion elements (column 11 lines 18-27 (quadrant detector generates an error signal which is used to drive azimuth and gimbal motors to correct for the error))(column 10 lines 30-45 (gimbal/azimuth motors allow for pointing bearings in a wide range of bearings, each node head is capable of rotating 370 degrees, other ranges are also permissible)).

With respect to claim 3, Chan discloses the optical wireless communication system in accordance with claim 1 (column 5 lines 55-64 (nodes are interconnected with one another by optical communication links, it is preferable that said links are wireless communication links)), wherein said fine optical axis adjusting means searches a region (column 37 lines 25-30 (scanning area has at worst a 10 by 10 degree uncertainty field)) wherein said light-receiving level information exceeds a predetermined value and executes the fine optical axis adjustment for the region identified by the search (column 37 lines 33-37 (once the corner cube is acquired, the beam can be directed to the receiver and the fine tuning can take place (wherein predetermined value is the value which allows for corner cube acquisition))).

Claim Rejections - 35 USC § 103

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

⁽a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Application/Control Number: 10/666,730

Art Unit: 2613

4. Claim 4 is rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 6,504,634 to Chan et al. in view of U.S. Patent No. 6,690,888 to Keller et al.

Page 6

With respect to claim 4, Chan discloses the optical wireless communication system in accordance with claim 1 (column 5 lines 55-64 (nodes are interconnected with one another by optical communication links, it is preferable that said links are wireless communication links)). However, Chan fails to disclose said fine optical axis adjusting means searches a relatively wide region when said light-receiving level information is relatively small, and said fine optical axis adjusting means searches a relatively narrow region when said light-receiving level information is relatively large. However, Keller, from the same field of endeavor discloses a method for establishing and maintaining optical open-air communications links (title) wherein when transmitted light crosses a receiver area such that the detected light experiences an increasing intensity, the search scanning area is decreased (column 10 lines 62-67). Therefore, it would have been obvious to one of ordinary skill in the art to implement the optical signal scanning method as taught by Keller in the optical scanning method as disclosed by Chan. The motivation for doing so would have been to decrease the amount of overall scanning time while also verifying that optical intensity is high enough for accurate data transmission (Keller: column 11 lines 1-6).

5. Claim 5 is rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 6,504,634 to Chan et al. in view of U.S. Patent No. 7,016,612 to Ikeda et al.

With respect to claim 5, Chan discloses the optical wireless communication system in accordance with claim 1 (column 5 lines 55-64 (nodes are interconnected with

one another by optical communication links, it is preferable that said links are wireless communication links)). However, Chan fails to disclose said fine optical axis adjusting means estimates a distance to said receiver based on said light-receiving level information, and accomplishes said fine optical axis adjustment. Ikeda, from the same field of endeavor estimates a distance between counterpart assemblies based on light receiving level information (column 13 17-41 (reception light intensity of the optical communication device is inversely proportional to the square of the distance))(Figures 11 and 12) to perform fine optical axis adjustment (column 13 lines 37-41 (reception light intensity level is judged and emission intensity is then adjusted according to the communication distance)). Therefore, it would have been obvious to one of ordinary skill in the art to implement the distance measurement as disclosed by Ikeda. The motivation for doing so would have been to create a more diverse optical axis alignment system that can compensate for a varying transmission distance.

Claim 6 is rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 6,504,634 to Chan et al. in view of U.S. Patent Application Publication No. 2002/0196506 to Graves et al.

With respect to claim 6, Chan discloses the optical wireless communication system in accordance with claim 1, however Chan fails to disclose halting transmission of an optical signal until a level of light is received at the receiver. Graves, from the same field of endeavor discloses an optical wireless communication system (atmospheric optical data transmission system (title)) a wherein transmitting said first optical signal by said first optical transmitting means is stopped until the light-receiving

Art Unit: 2613

level of said plurality of light-receiving elements of said second optical receiving means exceeds a predetermined value (page 9 paragraph 57 (components intermittently transmit and receive the light waves. When one transceiver is transmitting the other transceiver is only receiving and vise versa)). Therefore it would have been obvious to implement the halting transmission as taught by Graves in the communication system as taught by Chan. The motivation for doing so would have been to allow for time to adjust said transmission for non-ideal pulses such as pulses blocked by adverse atmospheric conditions (Graves: page 1 paragraph 2 (dust, smoke, fog)(page 1 paragraph 4 (system is adaptive to atmospheric aberrations)) and to save on optical power usage.

Conclusion

7. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. The following patents are cited to further show the state of the art with respect to coarse WDM data transmission in general:

Art Unit: 2613

U.S. Patent Application Publication No. 2004/0208598 is cited to show an optical transceiver pair

- U.S. Patent No. 5,065,455 is cited to show fine and coarse optical adjustment
- U.S. Patent Application Publication No. 2002/0131121 is cited to show an optical tracking method for an optical transceiver system
- U.S. Patent Application Publication No. 2002/0097472 is cited to show a reflection detection in an optical wireless link
- 8. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kenneth J. Malkowski whose telephone number is (571) 272-5505. The examiner can normally be reached on M-F 8:30-5:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ken Vanderpuye can be reached on (571) 272-3078. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2613

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

KJM 8/19/06

KENNETH VANDERPUYE SUPERVISORY PATENT EXAMINER